

	www.e4engineering.com	
18 April 2001	The 24-hour Service for Engineers and Industry	17:56 GMT

Search the site

Advanced Search...

click to clear!



» Home

e4engineering.com
[Events](#)

» Contents

[Latest news](#)
[Analysis](#)
[Comment](#)
[Features](#)
[Reuters Newsfeed](#)

» Channels

[Aerospace](#)
[Automotive](#)
[Business & Finance](#)
[Chemical & Process](#)
[Civil Engineering](#)
[Communications](#)
[Computers & IT](#)
[Controls](#)
[Electrical & Electronics](#)
[Environmental](#)
[Health & Safety](#)
[Machinery & Equipment](#)
[Mechanical](#)
[Medical](#)
[Recruitment](#)

» FAQ

[About E4](#)
[Technical Info](#)
[Who's Who](#)
[Privacy Policy](#)

» News

From **E4 : Engineering**, 27 March 2001, in **Chemical & Process**

Clay makes plastic fantastic

A researcher from Penn State University has found that small amounts of well-dispersed natural clay can lead to environmentally friendly and inexpensive plastic composites with improved specialised properties.

Addition of clay can make plastics less permeable to liquids and gases; more flame retardant and tougher. Lower permeability can make plastics like PET, the standard plastic used in soft drink bottling, suitable for bottling beer or wine as the clay-enhanced product would protect the beverages from the effects of oxygen.

'Adding very small amounts of natural clays to plastics changes some of their physical properties,' said Dr. Evangelos Manias, assistant professor of materials science and engineering. 'While we can tune the chemical interactions between the clays and some polymers, it is the general changes due to the nanometer fillers in all plastics that may be the most interesting.'


Adding clay to polymer blends is, however, said to be a difficult process but if the clay is treated with an organic surfactant, a compound that allows the inert clay to mix with the polymers, then the clays can be incorporated into the final product.

An inexpensive, more environmentally clean method of producing flame retardant plastics could eventually save lives. Because the addition of clay into plastics reduces flammability in a wide range of plastics, it may have universal application as a general flame-retardant additive, said Manias.

'Currently, chemicals used to make plastics flame retardant contain bromine, which produces poisonous combustion gases when burned,' said Manias. 'Using clay is a green alternative to current practices and reduces flammability in a wide range of plastics.' When polymers with clay incorporated in their structures burn, the clay forms a char layer on the outside of the plastic that insulates the material beneath, he added.

'Natural clays are currently the most used because they are the same clays already used in many products,' said Mania. 'However, synthetic clays, because of their tailored properties, may prove essential for high added value products, such as in biomedical devices and space applications.'

The natural clays Manias refers to are bentonites and montmorillonites that are already in use in paints, cosmetics and pharmaceuticals.



» On the Web

[PennState University](#)

» Related Stories

[Rolls-Royce win \\$12 million power deal](#)

» Also in

[Sports fans enjoy remote camera action](#)

[JAPAN: UPDATE 1-DAIMLER STICKS TO HYUNDAI,EYES M'BISHI TRUCK TIES.](#)

[SWEDEN: ERICSSON GETS \\$110 MLN PHILLIPPINE ORDER.](#)

[AUSTRALIA: AIR NZ PUTS GROUNDING COST AT NZ\\$2.5 MLN.](#)

[GERMANY: KPN THINKING ABOUT LINK UP WITH TIM-REPORT.](#)

» Related Channels

[Chemical & Process](#)
[Environmental](#)

The E4 Network «

e4engineering.com
e4data.com
e4jobnet.com
e4metals.com
e4subcontracting.com
e4overstock.com
[Respond To Me](#)



Magazines «

[The Engineer](#)
[Design Engineering](#)
[Process Engineering](#)
[Metalworking Production](#)
[Control & Instrumentation](#)
[Integrated Manufacturing Solutions](#)
[What's New In Industry](#)
subsonline.co.uk



Subscribe online now!

The polymer clay blends, while containing one to five percent clay, are actually nanocomposites and the addition of clay into the polymer blend does not alter the normal production and processing of the clayless polymer.

'The clay can be added at the final stages of polymer processing without any change in the current industrial practices,' said Manias. 'The thermodynamics drive the nanometer dispersion of the clay through the polymer and the small amounts of clay do not cause any wear in the equipment. Manufacturers can use the same equipment, timing and settings as in their normal process.'

While natural and synthetic clays provide a broad possibility of enhances plastics, Manias is also looking at polymer nanocomposites that contain platelets of metal and ceramic nanoparticles instead of clay. These ultra-small fillers may require different surfactants and offer much more flexibility in property tailoring, where cost can be slightly increased.

Copyright Centaur Communications Ltd. All rights reserved.
Read our [privacy policy](#). Technical queries to e4@centaurnet.co.uk.
Other queries to arvidj@centaur.co.uk.

The **e4** Network